



# Thermal Interface Materials

With electronic circuits becoming smaller and more powerful, thermal management has become a critical design parameter to prevent overheating and circuit failure. Thermal Interface Materials (TIMs) work by displacing air gaps between heat-generated components and heat sinks to help conduit heat out of the system.

## Thermally Conductive Adhesives

Thermally conductive and electrically insulating epoxy systems efficiently dissipate heat while providing a durable and structural permanent bond.

**One-part** 9460TC

**Two-part** 8329TFF, 8329TFS, 8349TFM, 8329TCS, 8329TCM

## Thermal Pastes

Thermal pastes create a non-permanent bond between heat-generating components and heat sinks.

**Silicone** 860

**Non-Silicone** 8616

## Thermal Gap Fillers

Silicone-based materials cure to a putty-like consistency that perfectly conform to gaps at the interface between heat-generating components and cooling plates.

**High Thermal Conductivity** TIA225GF

**Extreme Thermal Conductivity** TIA241GF

## Thermal Potting Compounds

Thermally conductive epoxy potting compounds protect printed circuit boards and electronic devices while offering heat dissipation from the system.

**Non-Flame Retardant** 832TC

**Flame Retardant** 834B, 834HTC, 834FX

## Supporting Products

Freeze sprays, also known as Super Colds, are aerosol cooling sprays for electronics.

**HFC-134a** 403A

**HFO 1234ze** 403C

## Applications

Thermal management

Heat dissipation

Bonding heat-sensitive components

Gap filling

## Industries

Battery modules and battery packs

Consumer electronics

LED manufacturing

Automotive

Aerospace

Defense

Instrumentation

Medical equipment

Research



MG Chemicals 1210 Corporate Drive, Burlington, Ontario, Canada L7L 5R6 [www.mgchemicals.com](http://www.mgchemicals.com)

NA: +(1)800-340-0772 Intl: +(1) 905-331-1396 EU: +(44)1663 362888 08 August 2022 - Version 1.0

# Thermal Interface Materials

	TC [W/(m-K)]	Working Time [min]	Mix Ratio [A:B]	Service Temp. [°C]	Mixed Viscosity [Pa-s]
<b>Thermally Conductive Adhesives</b>					
9460TC	0.8	Unlimited	One part	-65 to 150	Thixotropic paste
8329TFF	0.8	5	1:1	-40 to 150	Thixotropic paste
8349TFM	1.1	20	1:1	-50 to 150	260
8329TCM	1.4	45	1:1	-40 to 150	Thixotropic paste
8329TFS	1.2	240	1:1	-40 to 150	Thixotropic paste
8329TCS	1.4	240	1:1	-40 to 150	Thixotropic paste

## Thermal Pastes

860	0.7	—	—	-40 to 200	490
8616	2.0	—	—	-70 to 165	365

## Thermal Gap Fillers

TIA225GF	2.5	240	1:1	-45 to 200	100
TIA241GF	4.1	180	1:1	-45 to 200	130

## Epoxy Potting Compounds

832TC	0.7	120	1:1	-30 to 175	27
834B	0.8	60	2:1	-40 to 175	16
834FX	0.6	150	1:1	-50 to 125	15
834HTC	0.9	90	5:1	-50 to 150	10

## TIM Products Comparison Graph

